

**Extract from:**

**TRAFFIC SIGNS MANUAL – CHAPTER 8**

**Traffic Safety measures & signs for road works & temporary situations 2006**

**Part 2: Operations**

**Section 05 – General Vehicle Issues**

**05.5 TEMPORARY TRAFFIC MANAGEMENT VEHICLE SPECIFICATIONS**

05.5.1 Vehicles used for the installation, maintenance and removal of static traffic management on high-speed roads shall comply with the following specifications in paragraphs 05.5.2 to 05.5.5. Compliance with these specifications is also recommended for use on all types of highway irrespective of speed limit.

05.5.2 Inspection / Supervisor vehicles

- Conspicuous colour (yellow or white is recommended):
- 70mm capital letter height “HIGHWAY MAINTENANCE” sign to diagram 7404 (externally mounted on rear of vehicle) (see also paragraph 05.2.8):
- Roof-mounted amber light bar (visible 360 degrees) with a minimum of two independent light sources
- “Class ref 2” to BS EN 12899-1 or microprismatic reflective markings on the rear of the vehicle in accordance with paragraph 05.2.3 ( c ) or ( d ): and
- Company or client livery on side of vehicle.

05.5.3 Traffic management / maintenance vehicles (personnel / equipment carrier)

- Conspicuous colour (yellow or white is recommended):
- 140mm capital letter height “HIGHWAY MAINTENANCE” sign to diagram 7404 (externally mounted on rear of vehicle) (see also paragraph 05.2.8):
- “Class ref 2” to BS EN 12899-1 or microprismatic reflective markings on the rear of the vehicle in accordance with paragraph 05.2.3 ( c ) or ( d ):
- All seats shall be fitted with head restraints and 3 point inertia reel belts:
- Working lights:
- Reversing beeper: